

80/20 NICKEL CHROMIUM RIBBON RESISTANCE CHART

Width (mm)	Thickness (mm)	Resistance ohm/m		
		Min	Mean	Max
3.175	0.254	1.395	1.469	1.542
3.175	0.203	1.746	1.838	1.930
3.175	0.178	1.991	2.096	2.201
1.587	0.254	2.792	2.939	3.086
1.587	0.203	3.494	3.678	3.861
1.587	0.152	4.666	4.912	5.157
1.587	0.102	6.953	7.319	7.685
1.270	0.254	3.489	3.673	3.856
1.270	0.203	4.366	4.596	4.825
1.270	0.178	4.979	5.241	5.503
1.270	0.152	5.831	6.137	6.444
1.270	0.102	8.689	9.146	9.603
1.016	0.127	8.723	9.182	9.641
1.016	0.102	10.861	11.433	12.004
0.794	0.254	5.581	5.875	6.168
0.794	0.203	6.983	7.351	7.718
0.794	0.177	8.009	8.430	8.852
0.794	0.152	9.326	9.817	10.308
0.794	0.102	13.898	14.629	15.361
0.794	0.098	14.392	15.150	15.907
0.794	0.084	16.876	17.764	18.652
0.794	0.083	17.079	17.978	18.877
0.635	0.113	15.686	16.511	17.337
0.635	0.110	16.114	16.962	17.810

The data is from tests in our works and does not constitute a specification. No liability shall be implied or assumed from any data given.

Quality Assurance at all stages ensures very high standards.

RM80/20R-02/10